Air Guard 15,000



SAFETY DATA SHEET

Issue Date 4/6/16

Revision Date 5/17/16

Version 1

1. IDENTIFICATION

Product identifier	
Product Name:	Air Guard 15,000
Other means of identification	

Other means of identificationProduct code:F-603 (all grades)Synonyms:None

Recommended use of the chemical and restrictions on useRecommended Use:Lubricant.Uses advised against:No information available

Details of the supplier of the safety data sheet Supplier Address FRONTIER PERFORMANCE LUBRICANTS INC PO BOX 1777 LODL CA 95241

LODI, CA 95241 Phone: (800)-807-4496 Fax: (209)-334-6408

Emergency telephone number	
Emergency Telephone:	

PERS (800)-633-8253

2. HAZARDS IDENTIFICATION

Classification of the Mixture Most Important Hazards Hazard Category Signal Word Pictogram	Liquid, Slight petroleum odor. This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). Acute Oral Toxicity Category 4 Skin Irritation Category 2 Eye Irritation Category 2A Skin Sensitization Category 1B Warning!
Hazard Statements	Causes serious eye irritation. Causes skin sensitization with susceptible individuals. Causes eye, skin and respiratory tract irritation. Harmful if swallowed.
Precautionary Statements	
Prevention	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation. Do not eat, drink or smoke when using this product Wash thoroughly after handling.
Response Storage	Contaminated work clothing must not be allowed out of the workplace. Wash contaminated clothing before reuse. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention If on skin: wash with plenty of water. If swallowed, call a poison center/doctor if you feel unwell Keep container tightly closed. Store locked up
Disposal	Dispose of contents/containers in accordance with local and national regulations.

Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible, or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as
	probable, possible, or confirmed human carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as
	probable, possible, or confirmed human carcinogen by NTP

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	WT %	CAS #
Distillates, hydrotreated heavy paraffinic	0-95	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	0-95	64742-55-8

To the knowledge of the supplier, there are no other ingredients in this product that are classified as hazardous.

4. FIRST AID MEASURES Eyes Flush eyes with running water for at least 15 minutes. If redness, burning, blurred vision or irritation persists, transport to nearest medical facility for additional treatment. Skin Flush skin with water, wash with soap and water. If irritation occurs, get medical attention. Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment. Ingestion Do NOT induce vomiting and obtain medical attention. Have victim rinse mouth out with water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim Inhalation has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

5. FIRE-FIGHTING MEASURES

Flammable Properties Base Oil Flash point Flammable limits in air Auto ignition temperature	>210°C (ASTM D92) N/A N/A
Extinguishing media Special firefighting measure	CO ₂ , dry chemical, foam, alcohol-resistant foam, water mist Procedures for an oil fire should be utilized. Use self-contained breathing apparatus. Use foam or dry chemical to extinguish fire. Water may be used <u>only</u> to keep surrounding containers cool. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.
	6. ACCIDENTAL RELEASE MEASURES

Personal Precautions/Procedures: Use PPE and ensure adequate ventilation.

Environmental Precautions:Should not be released into the environment.
Do not contaminate water.
Do not flush to surface water or sanitary sewer system.

Methods and Materials for Containment/Clean Up:

Contain spillage, soak up with non-combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local/national regulations (see section 13).

7. HANDLING AND STORAGE

Handling and Storage Precautions Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls	Use adequate ventilation to keep vapors and mists of this material below applicable standards. Recommended work place control parameters - based on mineral oil ACGIH TWA 5 mg/m ³ .
Respiratory Protection	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.
Skin Protection	Use protective clothing that is chemically resistant to this product. Acceptable materials for gloves and aprons are: neoprene, nitrile rubber or viton.
Eye Protection	Use safety glasses or goggles. Have suitable eye wash water available.
Other/General Protection	For mists and vapors: Air purifying, organic vapor cartridge, NIOSH approved respirator. Use self-contained breathing apparatus for environments with unknown concentrations or emergency situations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Clear, Yellow	Vapor Pressure:	N/A	Solubility in Water:	Insoluble
Appearance:	Liquid	% Volatile by Volume:	N/A	Evaporation Rate	N/A
Odor:	Characteristic	Vapor Density (air = 1):	N/A	(Butyl Acetate = 1):	<1
Boiling Point:	N/A	Reactivity in Water:	Non-reactive	Specific Gravity:	0.80-0.91

10. STABILITY AND REACTIVITY

Stability	Stable
Conditions to avoid	Sources of ignition.
Incompatibility	Strong oxidizing or reducing agents.
Decomposition Products	Oxides of Carbon and Hydrogen.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure Potential Health Effects	Inhalation, skin, eyes and ingestion.
Eye Effects	Can cause irritation, redness, burns, and tissue destruction.
Skin Effects	Can cause inflammation, and significant irritation.
Oral Effects	Gastrointestinal tract irritation, nausea, and vomiting if swallowed.
Inhalation Effects	May cause respiratory tract irritation.
Chronic Health Effects	No data available to indicate product or components present in mixture are chronic health
	hazards.
Mutagenicity	Negative
Carcinogenicity	None anticipated
Reproductive Effects	Negative.
Teratogenicity	Negative.
Sensitization	See section 2
Toxicological Data	ATE oral is >2,000 mg/kg
	ATE dermal is > 4,000 mg/kg
	ATE inhalation (mist/aerosol) is estimated at 2.2 mg/L/4 h

12. ECOLOGICAL INFORMATION

Not classified due to inadequate data available on this mixture. Highly recommend avoidance of release to the environment.

13. DISPOSAL CONSIDERATIONS

Avoid release to the environment. Dispose in a safe manner in accordance with national, state and local regulations. Not a RCRA hazardous waste if uncontaminated. If "used" RCRA criteria must be determined. Dispose of container by recycling or if permitted incineration.

14. TRANSPORT INFORMATION

Proper Shipping Name

PETROLEUM LUBRICATING OIL; NOT REGULATED AS A HAZARDOUS MATERIAL FOR TRANSPORTATION UNDER 49 CFR. 65

Shipping Class

Dot Identification NumberN/ADot Shipping LabelNot regulated by DOT.TDG ClassificationNot controlled under TDG (Canada).

15. REGULATORY INFORMATION

U.S. Federal Regulatory Informat SARA 302 Threshold Planning Q SARA 304 Reportable Quantity SARA 311 Categories		N/A N/A
Acute Health Effects		None
Chronic Health Effects		None
Fire Hazard		No
Sudden Release of Pressur	re Hazard	No
Reactivity Hazard		No
EPA/TSCA Inventory	Listed	
EPA Hazard Classification Code	Not applicable	
CERCLA	No components are su	bject to reporting.
SARA Title III - Section 313 Supp	lier Notification	
	III, Section 313 and 40	
WHMIS Classification Other Regulations		iss D; Division 2, Subdivision B: otherwise causing toxic effects. formulation are listed on the CEPA-DSL (Domestic Substance List)

16. OTHER INFORMATION

NFPA Hazard Rating:

Health:	1	Slight
Flammability:	1	Slight
Reactivity:	0	Negligible

*Threshold Limit Value/Personal Exposure Limit

N/A = Not Applicable

N/E = Not Established

Issue Date	4/6/16
Revision Date	5/17/16
Revision Note	Not applicable

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet