

SAFETY DATA SHEET

Issue Date 4/15/2015 Revision Date 4/15/2015 Version 1

1. IDENTIFICATION

Product identifier

Product Name: Pure Guard FM Low Temp Chain Oil

Other means of identification

Product code: F-655 **Synonyms:** None

Recommended use of the chemical and restrictions on use

Recommended Use: Lubricant.

Uses advised against: No information available

Details of the supplier of the safety data sheet

Supplier Address

FRONTIER PERFORMANCE LUBRICANTS INC

PO BOX 1777 LODI, CA 95241 Phone: (800)-807-4496 Fax: (209)-334-6408

Emergency telephone number

Emergency Telephone: PERS (800)-633-8253

2. HAZARDS IDENTIFICATION

Classification of the Mixture Oil.

Most Important Hazards This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

Hazard Classification N/A
Signal Word N/A
Pictograms N/A
Hazard Statements N/A
Precautionary Statements N/A

Carcinogenicity:

IARC No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible, or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible, or confirmed human carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible, or confirmed human carcinogen by NTP.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient WT % CAS #

To the knowledge of the supplier, there are no other ingredients in this product that are classified as hazardous.

4. FIRST AID MEASURES

Eyes

Flush eyes with running water for at least 15 minutes. If redness, burning, blurred vision or irritation persists, transport to nearest medical facility for additional treatment.

Pure Guard FM Low Temp Chain Oil

Skin Flush skin with water, wash with soap and water. If irritation occurs, get medical attention.

Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Do NOT induce vomiting and obtain medical attention. Have victim rinse mouth out with water. If

vomiting occurs spontaneously, keep head below hips to prevent aspiration.

InhalationRemove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen

with rescue breathing or CPR as required and transport to the nearest medical facility.

5. FIRE-FIGHTING MEASURES

Flammable Properties

Ingestion

Base Oil Flash point: >200°C (ASTM D92) Flammable limits in air: N/A Auto ignition temperature: N/A

Extinguishing media Special firefighting measure CO₂, dry powder, foam, Alcohol-resistant foam, water mist

Procedures for an oil fire should be utilized. Use self-contained breathing apparatus. Use foam or dry chemical to extinguish fire. Water may be used <u>only</u> to keep surrounding containers cool. Firefighters should wear proper protective equipment and self-contained breathing apparatus

with full face piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions/Procedures: Use PPE and ensure adequate ventilation.

Environmental Precautions: Should not be released into the environment. Do not contaminate water. Do not flush to surface

water or sanitary sewer system.

Methods and Materials for Containment/Clean Up:

Contain spillage, soak up with non-combustible absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to

local/national regulations (see section 13).

7. HANDLING AND STORAGE

Handling and Storage Precautions Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof

ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Have appropriate fire extinguishers and spill clean-up equipment

in or near storage area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering ControlsUse adequate ventilation to keep vapors and mists of this material below applicable standards.

Recommended work place control parameters - based on mineral oil ACGIH TWA 5 mg/m³.

Respiratory Protection If engineering controls do not maintain airborne concentrations to a level which is adequate to

protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection

Standard, 29 CFR 1910.134.

Skin ProtectionUse protective clothing that is chemically resistant to this product. Acceptable materials for

gloves and aprons are: neoprene, nitrile rubber or viton.

Eye Protection Use safety glasses or goggles. Have suitable eye wash water available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Water White Vapor Pressure: N/A Solubility in Water: Insoluble Color: Appearance: % Volatile by Volume: **Evaporation Rate** Liquid N/A N/A Odor: Characteristic Vapor Density (air = 1): N/A (Butyl Acetate = 1): <1 **Boiling Point:** N/A Reactivity in Water: Non-reactive Specific Gravity: 0.8-0.9

10. STABILITY AND REACTIVITY

Stability Stable

Conditions to avoid Sources of ignition.

Pure Guard FM Low Temp Chain Oil

Incompatibility Strong oxidizing or reducing agents. **Decomposition Products** Oxides of Carbon and Hydrogen.

Hazardous Polymerization Will not occur.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure Inhalation, skin, eyes and ingestion.

Potential Health Effects

Eye Effects Can cause irritation, redness, burns, and tissue destruction.

Skin Effects Can cause inflammation, and significant irritation.

Oral Effects Gastrointestinal tract irritation, nausea, and vomiting if swallowed.

Inhalation Effects May cause respiratory tract irritation.

Chronic Health Effects

No data available to indicate product or components present in mixture are chronic health

hazards.

MutagenicityNegativeReproductive EffectsNot DeterminedTeratogenicityNot DeterminedSensitizationSee Section 2

Toxicological Data ATE oral is > 2,000 mg/kg

ATE dermal is > 4,000 mg/kg

ATE inhalation (mist/aerosol) is estimated at 2.17 mg/L/4 hour

12. ECOLOGICAL INFORMATION

Not classified due to inadequate data available on this mixture. Highly recommend avoidance of release to environment.

13. DISPOSAL CONSIDERATIONS

Avoid release to the environment. Dispose in a safe manner in accordance with national, state and local regulations. Not a RCRA hazardous waste if uncontaminated. If "used" RCRA criteria must be determined. Dispose of container by recycling or if permitted incineration.

14. TRANSPORT INFORMATION

Proper Shipping Name PETROLEUM OIL; NOT REGULATED AS A HAZARDOUS MATERIAL FOR

TRANSPORTATION UNDER 49 CFR.

Shipping Class 65 Dot Identification Number N/A

Dot Shipping Label Not regulated by DOT.

TDG Classification Not controlled under TDG (Canada).

15. REGULATORY INFORMATION

U.S. Federal Regulatory Information

SARA 302 Threshold Planning Quantity
SARA 304 Reportable Quantity
N/A
SARA 311 Categories

Acute Health Effects None
Chronic Health Effects None
Fire Hazard No

Sudden Release of Pressure Hazard No **Reactivity Hazard** No

EPA/TSCA Inventory Listed
EPA Hazard Classification Code Not applicable

CERCLA No components are subject to reporting.

SARA Title III - Section 313 Supplier Notification

No components listed in this product exceed the DE Minimus reporting level established by

SARA Title III< Section 313 and 40 CFR 372.

WHMIS Classification: See Section 2.

Other Regulations All components of this formulation are listed on the CEPA-DSL

16. OTHER INFORMATION

NFPA Hazard Rating:

Health:	1	Slight
Flammability:	1	Slight
Reactivity:	0	Negligible

*Threshold Limit Value/Personal Exposure Limit

N/A = Not Applicable N/E = Not Established

Issue Date4/15/2015Revision Date4/15/2015Revision NoteNot applicable

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet